

CABLE TIES

NYLON LOCKING CABLE TIES

Available Materials: Nylon 6/6, (natural)

Part No. C500 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm		
-1	.60	15	2.8	71	12	53
-2	.68	17	3.1	79	18	80
-3	.87	22	3.9	99		
-4	1.25	32	5.6	142		
-5	2.00	51	8.0	203		
-6	1.38	35	5.6	142		
-7	2.00	51	8.0	203		
-8	2.50	64	9.7	246	40	178
-9	3.00	76	11.4	290		
-10	4.00	102	14.6	371		
-11	1.00	25	4.8	122	50	222
-12	1.50	38	6.2	157		
-13	1.88	48	7.4	188		
-14	2.50	64	9.8	249		
-15	3.00	78	11.5	292		
-150	3.50	89	13.0	330		
-16	4.00	102	14.5	368		
-160	4.50	114	15.5	394		
-17	5.00	127	17.5	445		
-18	2.00	51	10.0	254	120	534
-180	2.50	64	8.4	213		
-19	3.00	76	11.4	290		
-20	4.00	102	14.5	368		
-200	6.00	152	21.9	556		
-21	7.00	178	24.7	627		
-22	8.00	203	27.6	701		
-23	9.00	229	30.5	775		
-24	10.31	262	34.3	871		
-25	5.00	127	17.7	450	175	778
-26	6.00	152	20.9	530		
-27	9.00	229	30.6	779		
-28	13.00	330	40.1	1100		
-29	2.00	51	9.0	228	250	1112
-30	5.00	127	20.1	510		
-31	6.00	152	22.2	563		
-32	8.00	203	28.3	718		
-33	10.00	254	34.2	868		
-34	12.00	305	40.1	1018		

NYLON RELEASABLE CABLE TIES

Available Materials: Nylon 6/6, (natural)

Part No. C501 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm		
-1	1.00	25	4.8	122	50	222
-2	1.50	38	6.3	160		
-3	1.88	48	7.4	188		
-4	3.00	76	11.5	292		
-5	4.00	102	14.5	368		
-6	2.00	51	8.4	213		
-7	3.00	76	11.4	290	80	356
-8	4.00	102	14.5	368		
-9	2.00	51	9.0	229		
-10	5.00	127	20.1	510		
-11	6.00	152	22.2	563	250	1112
-12	8.00	203	28.3	718		
-13	10.00	254	34.2	868		
-14	12.00	305	40.1	1018		

NYLON LOCKING CABLE TIES

For Outdoor Use in Acid Rain Environment

Available Materials: Nylon 12


Part No. C502 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm		
-1	1.38	34	5.6	142	25	111
-2	1.88	48	7.4	188	40	178
-3	4.00	102	14.5	368		
-4	4.00	102	14.5	368	90	399
-5	8.00	203	27.6	701		

TEMPERATURE RANGE:

- Nylon 6/6: -40°F to 185°F, -40°C to 85°C
- Nylon 12: -40°F to 176°F, -40°C to 80°C
- Flame Ret. Nylon: -40°F to 203°F, -40°C to 95°C
- Halar®: -50°F to 284°F, -46°C to 140°C
- Polypropylene: -40°F to 185°F, -40°C to 85°C
- Tefzel®: -50°F to 302°F, -46°C to 150°C

CABLE TIES (continued)



FLAME RETARDANT NYLON LOCKING CABLE TIES

Meets U.L. 94V-0

Available Materials: Flame Retardant Nylon

Part No. C503 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm	Lbs.	(N)
-1	.87	22	4.0	102	18	80
-2	1.88	48	7.4	188	50	222
-3	4.00	102	14.6	371	120	533

Additional sizes available.

HALAR® LOCKING CABLE TIES

For Outdoor Use in Acid Rain Environment

Plenum Applications

Available Materials: Halar®

Part No. C504 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm	Lbs.	(N)
-100	.87	22	4.0	102	18	80
-1	1.88	48	7.4	188	50	222
-2	3.00	78	11.60	295	50	222

POLYPROPYLENE RELEASABLE CABLE TIES

Chemical Resistant

Available Materials: Polypropylene

Part No. C505 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm	Lbs.	(N)
-1	2.00	51	9.0	229	90	400
-2	5.00	127	20.1	510		
-3	6.00	152	22.2	563		
-4	8.00	203	28.3	718		

Additional sizes available.

POLYPROPYLENE LOCKING CABLE TIES

Chemical Resistant

Available Materials: Polypropylene

Part No. C506 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm	Lbs.	(N)
-1	.87	22	3.9	99	11	49
-2	1.88	48	7.4	188		
-3	3.00	76	11.5	292	30	133
-4	4.00	102	14.5	368		
-5	2.00	51	8.4	213		
-6	3.00	76	11.4	290	50	222
-7	4.00	102	14.5	368		

Additional sizes available.

TEFZEL® LOCKING CABLE TIES

Nuclear and Harsh Environments

Available Materials: Tefzel®

Part No. C507 - (Size Code No.)

Size Code No.	Max. Bundle Diameter		Approx. Length		Min. Loop Tensile Strength Lbs. (N)	
	In.	mm	In.	mm	Lbs.	(N)
-1	.87	22	4.0	102	18	80
-2	2.00	51	8.0	203	25	111
-3	1.88	48	7.4	188	50	222
-4	3.00	76	11.6	295		
-5	4.00	102	14.6	371		
-6	3.00	78	11.5	292	120	533
-7	4.00	102	14.6	371		

TEMPERATURE RANGE:

Nylon 6/6: -40°F to 185°F, -40°C to 85°C
Nylon 12: -40°F to 176°F, -40°C to 80°C
Flame Ret. Nylon: -40°F to 203°F, -40°C to 95°C
Halar®: -50°F to 284°F, -46°C to 140°C
Polypropylene: -40°F to 185°F, -40°C to 85°C
Tefzel®: -50°F to 302°F, -46°C to 150°C