

INDEX by Entry

A

ABS, 35-51, 65-75, 109-110, 163-165, 167, 169, 174.

Acetal, 99-104, 126-131, 133, 135-137, 143-159.

(See also Delrin® and Celcon®.)

Acme,

Nuts, 173.

Threaded Rod, 173.

B

Beam Clamps, 7.

Beam Clips, 8.

Bumpers, self-adhesive, 191.

Binding Head Machine Screw, 18-19, 35, 54, 67, 78.

Bushings,

Circuit Board, 172.

Circuit Board Plug, 172.

Countersunk, 171.

Countersunk Circuit Board, 172.

Counterbore, 171.

Electrical,

Armor, 234.

Double Insulated, 232.

Open/Close, 230.

Shorty, 233.

Snap, 231-232.

Snub, 230.

Threaded Insulated, 234.

Universal, 233.

Shoulder, 164-165.

Strain Relief,

Bell Mouth, 275.

European Requirement, 276.

Mounting Hole Plug, 274.

Pigtail, 271-272.

Right Angle, 273-274.

Self-Locking, 266-267.

Straight Thru, 267-270.

Button Head Machine Screw, 37.

C

Cabinet Feet, 192.

Capacitor Mounts, 201.

Cable Mounts, 255.

Cable Ties, 241-242.

Cable Tie Mounts, 243-252.

Celcon®, 164-165, 174.

(See also Acetal® and Delrin®.)

Celcon® Glass-filled, 164-165, 174.

Cheese Head Machine Screw,

Metric, 30, 48, 60, 71, 82.

Clamps,

Cable, 257-258.

E-Z Twist Lock on Fin Clip Base, 257.

Hex Head Screw, 229.

Hose, 256.

Releasable, 253.

Releasable on Fin Clip Base, 257.

Stepless Ear, 229.

Clips,

Arrow, 179.

Keyhole, 179.

Latching, 255.

Spin, 175.

C (continued)

Connectors,

Liquid Tight Pigtail, 265.

Liquid Tight Straight-Thru, 263-264.

Right Angle, 263.

Snap-In, 262.

Cord Clips, 253-254.

Countersunk Head Screw

Metric, 47, 59, 70, 81, 99-104.

CPVC, 35-51, 76-86, 109-110, 126-131, 133, 135-137, 143-159, 163-165.

D

Delrin®, 35-51, 76-86, 99-104, 109-110, 163-165, 167-169, 174.

(See also Celcon® and Acetal®.)

Dowels, 178.

E

Engage 8400, 118.

Eye Bolts, 3.

Shoulder Eye Bolts, 3.

Expansion Screws, 203.

F

Feet, Nylon Drive Mounting, 177.

Feet, Cabinet, 192.

FEP®, 105-108, 126-131, 133, 135-137, 160-166.

Fiber Glass, G10, 35-51, 109-110, 126-131, 133, 135-137, 143-159, 163-165.

Fillister Head Machine Screw, 16, 37, 55, 66, 77.

Metric, 28, 47.

Flat Head Machine Screw, 20-21, 36, 55, 68, 79.

Metric, 31-32.

Flat Head Socket Machine Screw, 36.

G

Gears, 180-182.

Metric, 183-188.

Grommet Nuts, 194-195.

Grommets,

Edging, 260.

Spacer, 196.

Standard, 196.

Grub Screw,

Metric, slotted, 34.

H

Halar®, 35-51, 76-86, 105-110, 160-165.

Handles, 4.

Hex Fit Bolts,

Metric, 49, 61, 72, 83.

Hex Flanged Head Cap Screw, 57, 69, 80.

Metric, 73, 84.

Hex Head Cap Screw, 8, 23, 38, 56-57, 80.

Metric, 49, 61, 72, 82.

Slotted, 24, 29, 33.

Hex Head Machine Screw, 14-15, 37, 55.

Metric, 29, 48, 60, 71, 82.

Hex Socket Countersunk Head Screw,

Metric, 62, 73, 84.

H (continued)

Hex Socket Head Cap Screw, 38, 56.
 Metric, 33, 72, 83.
Hex Socket Head Machine Screw, 17, 67, 78.
Hex Socket Head Shoulder Screw, 38.
Hex Washer Head Cap Screw, 23.
Hose Fittings,
 Automotive, 212.
 Barbed, 183-185, 205-206, 224-225.
 Barbed Connectors, 207, 227.
 Barbed Elbow, 186, 208, 227.
 Barbed Tees, 209.
 Branch Tee, 208-209, 226-227.
 Dome Nut, 212.
 Elbow, 208.
 Female Luer, 214.
 Female Luer Bulkhead Mounting, 214.
 Female Luer Connector, 216.
 Female Luer Plug, 215.
 Female Luer Tee, 216.
 Female Luer for Threaded Ports, 214.
 Internally Threaded Tees, 210.
 Kynar, 217-223.
 Hole Plug, 216.
 Locking Nut, 216.
 Locking Sleeve, 210.
 Male Luer, 213, 215.
 Male Luer Plug, 215.
 Nipple, 211.
 Plugs, 211.
 Reducers, 211.
 Threaded Connectors, 207, 228.

I

Insulating Floats, 193.
Insulators,
 Screw, 166-168.
 Metric Screw, 166, 169.
Isoplast®, **30% Short Glass Fiber**, 10, 54-64, 93-95.
Isoplast®, **40% Long Glass Fiber**, 3-4, 9, 35-51, 93-95,
 109-110, 163-165, 173, 290-292.
Isoplast®, **60% Long Glass Fiber**, 7-8.

K

Knobs,
 Thumb Screw, 189-190.
Kynar® Hose Fittings, 217-223.
Kynar® (PVDF), 3, 35-51, 76-86, 99-110, 126-131, 133, 135-137,
 143-165, 167-174, 301.

L

Lexan®, 35-51, 109-110, 163-165, 167, 169, 174.
Leveling Foot, 5.

M

Military Standard Fasteners and Components, 260-261.
Metric Fasteners, 27-34, 47-51, 59-64, 70-75, 81-86, 98,
 114-115, 169, 174.

N

NAS, 259.
Noryl®, 35-51, 65-75, 109-110, 163-165, 167, 169, 174.

Nuts,

Cap, 89, 97.
Cap, metric, 91, 98.
Clamp, 93-96.
Flanged, 93-95.
 Acme, 173.
Grommet,
 Closed, 195.
 Double Split Square Head, 194.
 Round Head, 195.
 Standard, 196.
 Spacer, 196.
 Square Head, 194.
 Three Legged Square Head, 195.
Hex, 97, 93-96.
 Acme, 173.
 Jam, 88, 96.
 Metric, 91, 98.
Lock, 88-89, 270.
 Metric, 92.
Thumb, 89-90, 97.
Wing, 90.
 Metric, 92.
Nylatron GS, 99-104, 173-174.
Nylon, Flame Retardant, 258.
Nylon, Heat Stabilized, 99-104.
Nylon MDS, 99-104, 174.
Nylon 612, 74.
Nylon 6/6, 11, 34-51, 67-92, 99-104, 109-114, 143-159, 163-169,
 171-177, 194-201, 230-233, 257-258.
Nylon 6/6, 30% Glass-filled, 3, 35-51, 65-75, 109-110, 116-117,
 119-131, 133, 135-159, 163-165, 167-169, 171-174.
Nylon 46, Glass-filled, 35-51, 65-75, 109-110, 126-131, 133,
 135-137, 143-159, 163-165, 167-172, 297-298.
Nylon Super Tough, 35-51, 109-110, 163-165, 174.
O
Oval Head Machine Screw, 36.
 Metric, 31-32.

P

Pan Head Machine Screw, 11, 12, 35, 54, 65, 76.
 Metric, 27, 47, 59, 70, 81.
PFA (Teflon®), 35-51, 105-110, 143-165, 167-174.
PEEK®, 35-51, 65-75, 109-110, 126-131, 133, 136-137,
 163-165, 300.
Phenolic, 99-104.
Pipe Hanger, 9.
PCTFE, 35-51, 105-110, 126-131, 133, 135-137, 161-165, 167,
 169-170, 174.
Plugs,
 Electrical Applications,
 Dome, 235.
 Double "D", 237.
 Glossy, 238.
 Insulation, 239.
 Knock-out Seals, 240.
 Liquid Tight Knock-out Seals, 240.
 Pry Out, 238.
 Shorty, 236.
 Threaded, 236.
 Vent, 239.
 Window, 237.

INDEX by Entry (continued)

P (continued)

Polycarbonate, 4, 10, 126-131, 135-137, 143-159, 171-174.
(See also Lexan®.)
Polyethylene, 35-51, 99-104, 109-110, 163, 165, 171-173.
Polypropylene, 3, 35-51, 76-86, 99-104, 109-110, 126-131, 133, 135-137, 143-159, 163-165, 167-169, 171-173.
Polypropylene, Glass-filled, 3-5, 10, 65-75.
Polystyrene, 174.
Polysulfone, 35-51, 109-110, 163-165.
Post and Screw,
 Ratchet Assembly, 204.
 Rapid Assembly, 202-203.
Power Transistor Covers, 201.
Power Transistor Mounts, 200.
PPS, 30% Carbon Fiber, 54-64, 93-95.
Printed Circuit Board Fixtures, (See also Bushings).
 Circuit Board Locking Supports, 199.
 Circuit Board Posts, 198.
 Circuit Board Card Guides, 198.
 Two Piece Fasteners for Circuit Board Edge Connector Assembly, 198.
Push-in-Fasteners, 175.
PVC, 35-51, 99-104, 109-110, 126-131, 133, 135, 143-159, 163-165.

R

Radel®, 35-51, 54, 65-75, 93-95, 109-110, 293-296.
Raised Countersunk Head Screw,
 Metric, 47, 59, 70, 81.
Rivets, 178.
 Drive Rivets, 176.
 Two Place Anchor Rivets, 197.
 Snap Rivets, 176.
 Molded Rivets, 197.
Round Head Machine Screw, 13, 35, 54, 66, 77.
Ryton, (PPS), 7, 35-51, 54-64, 93-95, 109-110, 163-165, 299.

S

Set Screws,
 Chamfered End, Metric, 51, 64, 75, 86.
 Cone Point, 40, 45.
 Metric, 51, 64, 75, 86.
 Cup Point, 40.
 Metric, 51, 64, 75, 86.
 Dog Point, 40, 45.
 Metric, 51, 64, 75, 86.
 Flat Point, 40, 44.
 Metric, 51, 64, 75, 86.
 Large Size, 46.
 Oval Point, 40, 44.
 Plain Point, 43.
 Socket, 25.
 Slotted, 26.
Shelf Supports, Nylon Drive, 177.
Spacers,
 Cushioning, 118.
 Hex, 125.
 Hex, tapped, 125.
 Round, 119-123, 126-131, 132.
 Tapped, 124.
Spin Clips, 175.
Springs for Strain Relief Bushings, 272.

S (continued)

Standoffs,
 Hex, 135.
 Male-Female,
 Hex, 136-137.
 Round, 136-137.
 Round, 133.
 Wire, 258.
Straps, Hose, 256.

T

Teflon®, 35-51, 99-108, 126-131, 133, 135-137, 143-159, 160-165.
Tefzel®, 35-51, 105-108, 160-165, 258.
Terminal Strain Reliefs, 277.
Threaded Rod, 8, 174.
 Acme, 173.
 Metric, 174.
Thumb Screws, 41, 58.
 Knurled, 22, 42, 74.
 Metric, 33, 50, 63, 74, 85.
 Slotted, 22, 44.
 Metric, 50, 63, 74, 85.
Torlon®, 174.
Truss Head Machine Screw, 37.

U

U-Bolts, 278.
UHMW®, 35-51, 109-110, 163-165.
Ultem® 1000, 35-51, 65-75, 109-110, 167, 169, 169, 174
Ultem® 2300, 35-51, 65-75, 109-110, 167, 169, 169, 174.

V

Vespel®, 35-51, 109-110, 163-165.
Vinyl Ester, 8, 174.
Vented Screws, 52.

W

Washers,
 Cushioning, 118.
 Finishing, 117.
 Flat, 99-114, 118.
 Metric, 114-115.
 Large, 104.
 Retaining, 116.
 Shoulder, 138-163.