




Heyco® Nylon Drive Rivets

- Upon installation, the drive pin expands the rivet legs to lock components permanently and securely into place.
- Installation can be made "blind" from one side of the assembly.
- Resist vibration, and corrosion.
- Molded of type 6 nylon. Flammability classification 94V-2; temperature index 105° C.

CHASSIS DIMENSIONS						PART NO.	DESCRIPTION	HEAD STYLE	PART DIMENSIONS							
Mounting Hole Diameter		GRIPPING RANGE							A Length		B Head Height		C Head Diameter		D Drive Pin Diameter	
		Minimum	Maximum	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.	mm.
.122	3.1	.118	3.0	.157	4.0	2576	DR 122-118	Binder	.217	5.5	.079	2.0	.220	5.6	.075	1.7
.161	4.1	.079	2.0	.118	3.0	2578	DR 161-079	Round	.177	4.5	.118	3.0	.315	8.0	.100	2.5
.201	5.1	.079	2.0	.118	3.0	2580	DR 201-079	Truss	.197	5.0	.110	2.8	.374	9.5	.125	3.2
		.118	3.0	.157	4.0	2582	DR 201-118	Binder	.236	6.0						
		.157	4.0	.197	5.0	2584	DR 201-157	Binder	.276	7.0						
		.197	5.0	.236	6.0	2586	DR 201-197	Binder	.315	8.0						
		.236	6.0	.276	7.0	2588	DR 201-236	Binder	.354	9.0						

Standard Color: Black.



HEAD STYLES



BINDER



TRUSS



ROUND



Heyco Products, Inc.

"The First Name in Wire Protection"



800-453-1692

<http://www.AboveBoardElectronics.com>