


**NEW!**

Steel, Zinc Yellow



### HEX BODY, THIN HEAD THREADED INSERTS (RIVET NUTS)

Radius Corner Hex Body, Open End

Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M	Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M
HS-M43.00Y	M4X0.7X3.00	2,000	3.40	HS-M63.00Y	M6X1.0X3.00	2,000	8.91

**NEW!**

**METRIC**

Steel, Zinc Yellow



### ROUND RIBBED BODY, SMALL HEAD THREADED INSERTS (RIVET NUTS)


Small Flange, Thin Wall, Open End

Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M	Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M
LS-M43.20SY	M4X0.7X3.20	2,000	3.18	LS-M103.56SY	M10X1.50X3.56	1,000	14.70
LS-M63.20SY	M6X1.0X3.20	2,000	8.80	LS-M106.06SY	M10X1.50X6.06	1,000	15.80
LS-M65.70SY	M6X1.0X5.70	1,000	9.80				

**NEW!**

**METRIC**

Steel, Zinc Yellow



### ROUND RIBBED BODY, FLAT HEAD THREADED INSERTS (RIVET NUTS)


Large Flange, Open End

Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M	Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M
XS-M43.20SY	M4X0.7X2.00	2,000	3.50	XS-M65.70SY	M6X1.0X5.70	2,000	10.00
XS-M53.20SY	M5X0.8X3.20	2,000	4.58	XS-M83.20SY	M8X1.25X3.20	1,000	22.00
XS-M55.70SY	M5X0.8X5.70	2,000	4.85	XS-M103.56SY	M10X1.50X3.56	1,000	19.07

**NEW!**

**METRIC**

Aluminum Alloy # 5056



### FLAT HEAD THREADED INSERTS (RIVET NUTS)


Large Flange, Open End

Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M	Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M
XA-M42.00	M4X0.7X2.00	2,000	0.93	XA-M63.50	M6X1.0X3.50	2,000	3.30
XA-M43.00	M4X0.7X3.00	2,000	0.98	XA-M65.00	M6X1.0X5.00	2,000	3.50
XA-M53.50	M5X0.8X3.50	2,000	2.05	XA-M85.00	M8X1.25X5.00	1,000	5.05
XA-M55.00	M5X0.8X5.00	2,000	2.10	XA-M87.00	M8X1.25X7.00	1,000	5.20

**NEW!**

**METRIC**

Steel, Zinc Yellow



### ROUND BODY, FLAT HEAD THREADED INSERTS (RIVET NUTS)

Large Flange, Open End

Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M	Part #	Thread Size x Grip	Ctn Qty	Wght Lbs/M
XS-M42.00Y	M4X0.7X2.00	2,000	2.88	XS-M63.50Y	M6X1.0X3.50	2,000	9.88
XS-M43.00Y	M4X0.7X3.00	2,000	3.00	XS-M65.00Y	M6X1.0X5.00	2,000	10.25
XS-M53.50Y	M5X0.8X3.50	2,000	6.10	XS-M85.00Y	M8X1.25X5.00	1,000	7.12
XS-M55.00Y	M5X0.8X5.00	2,000	1.73	XS-M87.00Y	M8X1.25X7.00	1,000	7.62

**NEW!**

**METRIC**

Carbon Steel Thermal Black



Plain Spring Pins appear black in color but have no black colored finish applied

### SLOTTED TYPE SPRING PINS

Manufactured to ISO 8752 specifications  
Hardened and tempered to Vickers 420 HV30 - 520 HV30

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
MI0204PS	M2X4	20,000	0.13	MI0340PS	M3X40	5,000	3.04
MI0205PS	M2X5	20,000	0.16	MI0345PS	M3X45	2,500	3.43
MI0206PS	M2X6	20,000	0.19	MI0350PS	M3X50	2,500	3.83
MI0208PS	M2X8	20,000	0.27				
MI0210PS	M2X10	20,000	0.36	MI3.506PS	M3.5X6	10,000	0.54
MI0212PS	M2X12	20,000	0.42	MI3.508PS	M3.5X8	10,000	0.79
MI0214PS	M2X14	20,000	0.49	MI3.510PS	M3.5X10	10,000	1.03
MI0216PS	M2X16	20,000	0.56	MI3.512PS	M3.5X12	10,000	1.23
MI0218PS	M2X18	20,000	0.63	MI3.514PS	M3.5X14	10,000	2.90
MI0220PS	M2X20	20,000	0.71	MI3.516PS	M3.5X16	10,000	1.66
MI0222PS	M2X22	10,000	0.78	MI3.518PS	M3.5X18	10,000	1.89
MI0224PS	M2X24	10,000	0.85	MI3.520PS	M3.5X20	10,000	2.08
MI0226PS	M2X26	10,000	0.93	MI3.522PS	M3.5X22	10,000	2.30
MI0228PS	M2X28	10,000	1.00	MI3.524PS	M3.5X24	5,000	2.52
MI0230PS	M2X30	10,000	1.08	MI3.525PS	M3.5X25	5,000	2.62
				MI3.526PS	M3.5X26	5,000	2.68
MI2.504PS	M2.5X4	20,000	0.19	MI3.528PS	M3.5X28	5,000	2.92
MI2.505PS	M2.5X5	20,000	0.25	MI3.530PS	M3.5X30	5,000	3.09
MI2.506PS	M2.5X6	20,000	0.30	MI3.532PS	M3.5X32	5,000	3.31
MI2.508PS	M2.5X8	20,000	0.42	MI3.535PS	M3.5X35	5,000	3.64
MI2.510PS	M2.5X10	20,000	0.53	MI3.536PS	M3.5X36	5,000	3.68
MI2.512PS	M2.5X12	20,000	0.64	MI3.540PS	M3.5X40	5,000	4.10
MI2.514PS	M2.5X14	20,000	0.74	MI3.545PS	M3.5X45	2,500	4.72
MI2.516PS	M2.5X16	20,000	0.81	MI3.550PS	M3.5X50	2,500	5.25
MI2.518PS	M2.5X18	20,000	0.94	MI3.560PS	M3.5X60	2,500	6.33
MI2.520PS	M2.5X20	10,000	1.06				
MI2.522PS	M2.5X22	10,000	1.19	MI0406PS	M4X6	10,000	0.72
MI2.524PS	M2.5X24	10,000	1.29	MI0408PS	M4X8	10,000	1.03
MI2.526PS	M2.5X26	10,000	1.41	MI0410PS	M4X10	10,000	1.31
MI2.528PS	M2.5X28	10,000	1.53	MI0412PS	M4X12	10,000	1.63
MI2.530PS	M2.5X30	10,000	1.64	MI0414PS	M4X14	10,000	1.87
				MI0416PS	M4X16	10,000	2.18
MI0305PS	M3X5	20,000	0.34	MI0418PS	M4X18	10,000	2.43
MI0306PS	M3X6	20,000	0.44	MI0420PS	M4X20	10,000	2.73
MI0308PS	M3X8	20,000	0.61	MI0422PS	M4X22	5,000	3.00
MI0310PS	M3X10	20,000	0.74	MI0424PS	M4X24	5,000	3.29
MI0312PS	M3X12	20,000	0.90	MI0425PS	M4X25	5,000	3.41
MI0314PS	M3X14	20,000	1.04	MI0426PS	M4X26	5,000	3.55
MI0316PS	M3X16	10,000	1.20	MI0428PS	M4X28	5,000	3.81
MI0318PS	M3X18	10,000	1.36	MI0430PS	M4X30	5,000	4.10
MI0320PS	M3X20	10,000	1.56	MI0432PS	M4X32	5,000	4.38
MI0322PS	M3X22	10,000	1.64	MI0435PS	M4X35	5,000	4.75
MI0324PS	M3X24	10,000	1.81	MI0436PS	M4X36	5,000	4.88
MI0326PS	M3X26	10,000	1.98	MI0440PS	M4X40	2,500	5.44
MI0328PS	M3X28	10,000	2.13	MI0445PS	M4X45	2,500	6.13
MI0330PS	M3X30	5,000	2.21	MI0450PS	M4X50	2,500	6.88
MI0332PS	M3X32	5,000	2.38	MI0460PS	M4X60	2,500	8.38
MI0334PS	M3X34	5,000	2.58				
MI0336PS	M3X36	5,000	2.72				



NEW!

METRIC

Carbon Steel Thermal Black



Plain Spring Pins appear black in color but have no black colored finish applied

SLOTTED TYPE SPRING PINS


Manufactured to ISO 8752 specifications
Hardened and tempered to Vickers 420 HV30 - 520 HV30

Table with 8 columns: Part #, Size, Ctn Qty, Wght Lbs/M, Part #, Size, Ctn Qty, Wght Lbs/M. Lists various slotted type spring pin specifications.

NEW!

METRIC

Steel Zinc



Free Manufacturer's Certifications Available

ISO 7380 SIX-LOBE BUTTON HEAD CAP SCREW / CLASS 10.9

Manufactured to ISO 7380 dimensions
Heads to ASME B18.3.4M with Six-Lobe Recess
Heat Treated Class 10.9 Steel, Zinc Plate

Table with 12 columns: Part #, Size, Ctn Qty, Wght Lbs/M, Part #, Size, Ctn Qty, Wght Lbs/M. Lists various ISO 7380 six-lobe button head cap screw specifications.

NEW!

METRIC

A2 Stainless



ISO 7380 SIX-LOBE BUTTON HEAD CAP SCREW

Manufactured to ISO 7380 dimensions
Heads to ASME B18.3.4M with Six-Lobe Recess
A2 Stainless Steel

Table with 12 columns: Part #, Size, Ctn Qty, Wght Lbs/M, Part #, Size, Ctn Qty, Wght Lbs/M. Lists various ISO 7380 six-lobe button head cap screw specifications for A2 stainless steel.

