

Body: Aluminum Alloy*
Mandrel: Low Carbon Steel*



DOMED HEAD MULTI-GRIP BLIND RIVETS

Body: *Aluminum Alloy #5251 or equivalent
Mandrel: *Low Carbon Steel, Black Phosphate Coated

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
D-0410B	1/8X.031-.187	10,000	2.20	D-0613B	3/16X.062-.250	5,000	5.95
D-0414B	1/8X.125-.312	10,000	2.52	D-0619B	3/16X.187-.437	4,000	6.75
D-0512B	5/32X.046-.250	6,000	3.81				
D-0516B	5/32X.156-.375	6,000	4.41				

Body: Aluminum Alloy*
Mandrel: Steel Zinc Yellow*



BRAZIER HEAD MULTI-GRIP BLIND RIVETS

Shear Strength: 159 lbs • Tensile Strength: 240 lbs
Body: *Aluminum Alloy #5052
Mandrel: *Steel Zinc Yellow #1018

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
B-3716	3/16x.18-.44	4,000	6.71	B-3722	3/16x.06-.25	4,000	7.54

Body: Steel Zinc*
Mandrel: Steel Zinc*




COUNTERSUNK HEAD MULTI-GRIP BLIND RIVETS

Body: *Low Carbon Steel Zinc Plate
Mandrel: *Low Carbon Steel Zinc Plate

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
SF48110K	3/16X.098-.236	5,000	7.52	SF48220K	3/16X.354-.670	2,000	10.78
SF48140K	3/16X.188-.354	4,000	8.56				
SF48170K	3/16X.157-.472	4,000	9.13				

Body: Steel Zinc*
Mandrel: Steel Zinc*



Items marked with "*" are Zinc Yellow Plated

DOMED HEAD MULTI-GRIP BLIND RIVETS

Body: *Low Carbon Steel Zinc Plate
Mandrel: *Low Carbon Steel Zinc Plate

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
SF32090D	1/8X.043-.157	10,000	3.43	SF48110D	3/16X.039-.236	5,000	8.71
SF32130D	1/8X.039-.354	8,000	3.81	SF48140D	3/16X.039-.354	4,000	9.66
SF40110D	5/32X.055-.197	6,000	6.49	SF48170D	3/16X.188-.472	4,000	10.34
SF40140D	5/32X.055-.315	6,000	7.75	*SF48140DY	3/16X.039-.354	4,000	9.70
				*SF48170DY	3/16X.188-.472	4,000	10.34

Body: Steel Zinc*
Mandrel: Steel Zinc*



LARGE FLANGE MULTI-GRIP BLIND RIVETS

Body: *Low Carbon Steel Zinc Plate
Mandrel: *Low Carbon Steel Zinc Plate

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
SF48110L	3/16X.039-.236	3,000	11.66	SF48170L	3/16X.118-.472	2,500	13.29
SF48140L	3/16X.039-.354	3,000	12.61				

Body: Low Carbon Steel*
Mandrel: Low Carbon Steel*



LOW-PROFILE MULTI-GRIP BLIND RIVETS

Body: *Low Carbon Steel, Zinc Plate
Mandrel: *Low Carbon Steel, Zinc Plate

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
LS-0411	1/8x.04-.11	10,000	3.40	LS-0612	3/16x.04-.18	4,000	8.70
LS-0514	5/32x.05-.19	6,000	6.50	LS-0616	3/16x.15-.25	4,000	9.80

Body: Stainless
Mandrel: Stainless



PROTRUDING HEAD STRUCTURAL HIGH STRENGTH BLIND RIVETS

*Body: 300-series Stainless Steel
*Mandrel: 300-series Stainless Steel

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
PSS86	1/4X.080-.375	500	19.00	PSS810	1/4X.350-.625	250	22.25

Body: Aluminum Alloy*
Mandrel: Aluminum Alloy*



PROTRUDING HEAD STRUCTURAL HIGH STRENGTH BLIND RIVETS

*Body: Aluminum Alloy #5056, Clear Chromate
*Mandrel: Aluminum Alloy #7075, Gold Chromate

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
PA64	3/16X.062-.270	4,000	3.07	PA86	1/4X.080-.375	2,000	7.10
PA67	3/16X.214-.437	3,500	3.50	PA810	1/4X.350-.625	1,800	8.38



Body: Steel*
Mandrel: Steel*



PROTRUDING HEAD STRUCTURAL HIGH STRENGTH BLIND RIVETS

*Body: Low Carbon Steel, Zinc w/ Clear Chromate
*Mandrel: Medium Carbon Steel

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
Part Number Comparison Chart at www.kanebridge.com							
PS67M	3/16X.062-.437	3,000	9.80	PS810	1/4X.350-.625	1,800	23.67
				PS822	1/4X1.080-1.37	500	32.50
				PS810M	1/4X.080-.625	1,600	23.50
				PS86	1/4X.080-.375	2,000	19.90

Body: Low Carbon Steel*
Mandrel: Low Carbon Steel*



Items marked with "*" are available on a special order basis only and not regularly in stock.

DOME HEAD ORLOCK® HIGH STRENGTH BLIND RIVETS

Double Locking, Water Resistant, Vibration Proof
Body: *Low Carbon Steel, Zinc Plate
Mandrel: *Low Carbon Steel, Zinc Plate

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
Part Number Comparison Chart at www.kanebridge.com							
L48090P	3/16X.06-.14	5,000	9.11	LS65205P	1/4X.43-.57	2,000	24.12
				LS65225P	1/4X.51-.65	2,000	25.15
L48115P	3/16X.14-.23	4,000	10.08	L78135P	5/16X.16-.28	1,000	34.00
L48140P	3/16X.24-.33	3,000	10.49	L78165P	5/16X.28-.39	1,000	36.20
L48165P	3/16X.34-.43	3,000	11.24	L78195P	5/16X.39-.51	1,000	38.40
L48190P	3/16X.43-.53	3,000	11.66				
LS65105P	1/4X.08-.17	2,000	19.80	L78225P	5/16X.51-.63	1,000	40.70
LS65125P	1/4X.12-.25	2,000	20.57	L78255P	5/16X.63-.75	1,000	42.30
LS65145P	1/4X.20-.33	2,000	20.98				
LS65165P	1/4X.28-.41	2,000	22.00				

Body: Aluminum Alloy*
Mandrel: Aluminum Almg*



Items marked with "*" are available on a special order basis only and not regularly in stock

COUNTERSUNK ORLOCK® HIGH STRENGTH BLIND RIVETS

Double Locking, Water Resistant, Vibration Proof
Body: *Aluminum Alloy #5052
Mandrel: *Aluminum Almg 6.0 or equivalent

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
LH64195K	1/4X.46-.54	2,000	6.64	LH64215K	1/4X.54-.62	2,000	7.08

Body: Aluminum Alloy*
Mandrel: Aluminum Almg*



Items marked with "*" are available on a special order basis only and not regularly in stock

DOME HEAD ORLOCK® HIGH STRENGTH BLIND RIVETS

Double Locking, Water Resistant, Vibration Proof
Body: *Aluminum Alloy #5052
Mandrel: *Aluminum Almg 6.0 or equivalent

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
LH64105P	1/4X.11-.19	2,000	6.60	LH64165P	1/4X.35-.43	2,000	7.37
LH64125P	1/4X.19-.26	2,000	6.78	LH64185P	1/4X.43-.50	2,000	7.70
LH64145P	1/4X.27-.34	2,000	7.04	LH64205P	1/4X.50-.58	2,000	7.98

Body: Steel Zinc Yellow*
Mandrel: Steel Zinc Yellow*



Items marked with "*" are available on a special order basis only and not regularly in stock

COUNTERSUNK ORLOCK® HIGH STRENGTH BLIND RIVETS

Double Locking, Water Resistant, Vibration Proof
Body: Low Carbon Steel, Zinc Yellow
Mandrel: Carbon Steel, Zinc Yellow

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
L64195K	1/4X.47-.54	2,000	18.72				

Body: 18-8 Stainless Steel
Mandrel: 18-8 Stainless Steel



DOME ORLOCK® HIGH STRENGTH BLIND RIVETS

Double Locking, Water Resistant, Vibration Proof
All items are available on a special order basis & not regularly in stock

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
LN64105P	1/4X.07-.19	2,000	19.30	LN64165P	1/4X.27-.42	2,000	22.12
LN64125P	1/4X.15-.27	2,000	20.11	LN64185P	1/4X.35-.50	2,000	23.32
LN64145P	1/4X.19-.35	2,000	21.13				

Body: Aluminum
Mandrel: Aluminum



For use in irregular and oversized holes

3-STAR™ BULBING TYPE BLIND RIVETS

Shear Strength: 5/32 diam - 112 lbs; 3/16 diam - 202 lbs
Tensile Strength: 5/32 diam - 225 lbs; 3/16 diam - 247 lbs

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
Part Number Comparison Chart at www.kanebridge.com							
ADATSB-0516	5/32X.039-.118	3,000	2.07	ADATSB-0619	3/16X.039-.118	2,000	3.39
ADATSB-0523	5/32X.039-.275	2,000	2.34	ADATSB-0625	3/16X.039-.354	2,500	3.69
				ADATSB-0630	3/16X.157-.472	1,200	4.12

Body: Aluminum
(Black Anodized)
Mandrel: Aluminum



For use in irregular and oversized holes

3-STAR™ BULBING TYPE BLIND RIVETS

Shear Strength: 5/32 diam - 112 lbs; 3/16 diam - 202 lbs
Tensile Strength: 5/32 diam - 225 lbs; 3/16 diam - 247 lbs

Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M	Part #	Diameter x Grip Range	Ctn Qty	Wght Lbs/M
ADATSB-0523B	5/32X.039-.275	2,000	2.34	ADATSB-0619B	3/16X.039-.118	2,000	3.39
				ADATSB-0625B	3/16X.039-.354	2,500	3.69

