


Steel Zinc Plated




Items marked with "•" have #2 point; all others have #3 point

HEX WASHER UNSLOTTED
SELF DRILLING SCREWS WITH NEO-EPDM WASHER

Used in metal roofing to create a leak-proof seal
Screw is Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
•0808KWN	8-18X1/2	4,000	4.92	1408KWN	1/4-14X1/2	1,000	10.24
•0810KWN	8-18X5/8	3,000	5.33	1412KWN	1/4-14X3/4	1,000	15.00
•0812KWN	8-18X3/4	2,000	7.00	1414KWN	1/4-14X7/8	1,000	15.75
•0816KWN	8-18X1	2,000	8.00	1416KWN	1/4-14X1	1,000	17.60
•0820KWN	8-18X1 1/4	2,000	9.00	1420KWN	1/4-14X1 1/4	1,000	20.00
•0824KWN	8-18X1 1/2	2,000	10.00	1424KWN	1/4-14X1 1/2	1,000	22.50
•0832KWN	8-18X2	2,000	12.00	1428KWN	1/4-14X1 3/4	1,000	23.25
				1432KWN	1/4-14X2	1,000	27.33
•1008KWN	10-16X1/2	2,000	5.06	1440KWN	1/4-14X2 1/2	750	33.00
1010KWN	10-16X5/8	2,000	8.00	1448KWN	1/4-14X3	500	39.00
1012KWN	10-16X3/4	2,000	8.30	1456KWN	1/4-14X3 1/2	500	40.08
1014KWN	10-16X7/8	2,000	7.80	1464KWN	1/4-14X4	300	43.75
1016KWN	10-16X1	2,000	10.67	1480KWN	1/4-14X5	200	53.00
1020KWN	10-16X1 1/4	2,000	12.00	1496KWN	1/4-14X6	100	61.50
1024KWN	10-16X1 1/2	2,000	13.00				
1032KWN	10-16X2	1,500	15.33	3112KWN	5/16-12X3/4	1,000	26.30
1040KWN	10-16X2 1/2	1,250	16.10	3116KWN	5/16-12X1	1,000	26.00
1048KWN	10-16X3	1,000	18.65	3120KWN	5/16-12X1 1/4	700	28.80
				3124KWN	5/16-12X1 1/2	600	37.50
1212KWN	12-14X3/4	2,000	12.33	3132KWN	5/16-12X2	600	45.33
1214KWN	12-14X7/8	1,500	13.00	3140KWN	5/16-12X2 1/2	600	52.83
1216KWN	12-14X1	1,500	14.00	3148KWN	5/16-12X3	300	55.00
1220KWN	12-14X1 1/4	1,500	16.00				
1220KWN	12-14X1 1/4	1,500	16.00	3708KWN	3/8-12X1/2	1,000	28.00
1224KWN	12-14X1 1/2	1,500	17.50	3712KWN	3/8X12-3/4	750	38.20
1232KWN	12-14X2	1,000	22.67	3716KWN	3/8-12X1	750	41.40
1240KWN	12-14X2 1/2	750	33.00	3724KWN	3/8-12X1 1/2	600	59.00
1248KWN	12-14X3	750	25.17				
1264KWN	12-14X4	500	31.75				

Steel Zinc Plated



All items have #5 point


#5 POINT HEX WASHER UNSLOTTED
SELF DRILLING SCREWS WITH NEO-EPDM WASHER

Screw is Case Hardened to Rockwell C52 - 58
(Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
1220KWN5	12-14X1 1/4	1,500	12.17	1232KWN5	12-14X2	1,000	17.00
1224KWN5	12-14X1 1/2	1,500	13.80	1248KWN5	12-14X3	750	24.15

NEW!

410 Stainless Steel with Black Oxide finish



Items marked with "•" have #2 point; all others have #3 point

HEX WASHER UNSLOTTED
SELF DRILLING SCREWS

Manufactured to B18.6.3 & SAE J78 dimensions

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
•0808KW410B	8-18X1/2	5,000	3.20	1412KW410B	1/4-14X3/4	2,000	11.60
•0812KW410B	8-18X3/4	5,000	4.10	1416KW410B	1/4-14X1	2,000	13.60
•1008KW410B	10-16X1/2	4,000	4.70				
1012KW410B	10-16X3/4	4,000	5.80				

Case Hardened Steel
Black Phosphate Finish




BUGLE PHILLIPS
DRYWALL SCREWS

Fine Thread - Self Drilling Point
Case Hardness: Rockwell C44 minimum

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
•0608KPG	6-20X1/2	10,000	1.77	•0836KPG	8-18X2 1/4	2,000	8.30
•0612KPG	6-20X3/4	10,000	2.90	•0838KPG	8-18X2 3/8	2,000	8.74
•0616KPG	6-20X1	10,000	3.25	•0840KPG	8-18X2 1/2	2,000	9.70
•0618KPG	6-20X1 1/8	10,000	3.61	•0842KPG	8-18X2 5/8	1,600	10.14
•0620KPG	6-20X1 1/4	8,000	3.85	•0848KPG	8-18X3	1,400	11.45
•0622KPG	6-20X1 3/8	7,000	4.15	•0856KPG	8-18X3 1/2	1,000	17.40
•0624KPG	6-20X1 1/2	5,000	4.15	•0864KPG	8-18X4	1,000	15.25
•0626KPG	6-20X1 5/8	5,000	4.46				
•0628KPG	6-20X1 3/4	4,000	5.00	1020KPG	10-16X1 1/4	2,000	8.00
•0630KPG	6-20X1 7/8	4,000	5.50	1022KPG	10-16X1 3/8	2,000	8.20
•0632KPG	6-20X2	4,000	5.51	1024KPG	10-16X1 1/2	2,000	8.50
•0636KPG	6-20X2 1/4	4,000	5.70	1032KPG	10-16X2	1,500	9.00
•0640KPG	6-20X2 1/2	3,000	7.22	1040KPG	10-16X2 1/2	1,000	13.40
•0648KPG	6-20X3	2,000	7.86	1056KPG	10-16X3 1/2	1,000	17.75
				1064KPG	10-16X4	500	21.00
•0716KPG	7-19X1	10,000	3.66	1072KPG	10-16X4 1/2	400	22.30
•0720KPG	7-19X1 1/4	8,000	4.55	1088KPG	10-16X5 1/2	300	27.25
•0726KPG	7-19X1 5/8	5,000	5.13	1096KPG	10-16X6	300	32.02
•0730KPG	7-19X1 7/8	4,000	6.15				
•0732KPG	7-19X2	4,000	7.03	1264KPG	12-14X4	500	26.25
				1280KPG	12-14X5	250	32.87
•0808KPG	8-18X1/2	3,000	2.37				
•0812KPG	8-18X3/4	3,000	4.20	1464KPG	1/4-14X4	300	35.00
•0816KPG	8-18X1	3,000	4.20	1480KPG	1/4-14X5	250	43.75
•0820KPG	8-18X1 1/4	2,500	5.00				
•0824KPG	8-18X1 1/2	2,000	6.01	3120KPG	5/16-12X1 1/4	700	18.33
•0826KPG	8-18X1 5/8	2,000	6.40				
•0828KPG	8-18X1 3/4	2,000	6.50	3732KPG	3/8-12X2	600	62.00
•0832KPG	8-18X2	2,000	7.87				

Steel Black Oxide



Items marked with "•" have #2 point; all others have #3 point


FLAT PHILLIPS
SELF DRILLING SCREWS

Combination Phillips and Slotted Recess
Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
•0606KPFB	6-20X3/8	10,000	1.46	1216KPFB	12-14X1	4,000	9.70
•0608KPFB	6-20X1/2	10,000	1.77				
•0808KPFB	8-18X1/2	10,000	2.67	1412KPFB	1/4-14X3/4	3,000	9.78
•0812KPFB	8-18X3/4	10,000	3.50	1416KPFB	1/4-14X1	3,000	11.68
•0816KPFB	8-18X1	8,000	3.79	1420KPFB	1/4-14X1 1/4	2,000	13.47
				1424KPFB	1/4-14X1 1/2	2,000	15.47
•1008KPFB	10-16X1/2	10,000	3.66	1432KPFB	1/4-14X2	1,000	18.50
1012KPFB	10-16X3/4	8,000	4.13	1440KPFB	1/4-14X2 1/2	1,000	25.00
1016KPFB	10-16X1	6,000	5.96				
1020KPFB	10-16X1 1/4	5,000	6.85				
1024KPFB	10-16X1 1/2	4,000	8.10				



Steel Black Oxide




Items marked with “*” have #2 point; all others have #3 point

**HEX WASHER PHILLIPS
SELF DRILLING SCREWS**

Manufactured to SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0810KPWB	8-18X5/8	10,000	3.40	1016KPWB	10-16X1	4,000	6.60

Steel Black Oxide



Items marked with “*” have #2 point; all others have #3 point

**OVAL PHILLIPS
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0812KPOB	8-18X3/4	10,000	3.61	1012KPOB	10-16X3/4	7,000	5.19
*0816KPOB	8-18X1	7,000	4.73	1016KPOB	10-16X1	5,000	6.13
*0820KPOB	8-18X1 1/4	5,000	5.72	1020KPOB	10-16X1 1/4	4,000	8.00
*0824KPOB	8-18X1 1/2	4,000	6.60				

Steel Black Oxide




Items marked with “*” have #2 point; all others have #3 point

**PAN PHILLIPS
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0408KPPB	4-24X1/2	10,000	1.14	*1008KPPB	10-16X1/2	8,000	4.40
*0606KPPB	6-20X3/8	10,000	1.69	*1010KPPB	10-16X5/8	8,000	4.96
*0608KPPB	6-20X1/2	10,000	2.06	1012KPPB	10-16X3/4	7,000	5.51
*0610KPPB	6-20X5/8	10,000	2.28	1016KPPB	10-16X1	5,000	6.93
*0612KPPB	6-20X3/4	10,000	2.77	1020KPPB	10-16X1 1/4	4,000	7.96
*0616KPPB	6-20X1	10,000	3.19	1032KPPB	10-16X2	2,000	12.56
*0620KPPB	6-20X1 1/4	9,000	3.66	1064KPPB	10-16X4	1,000	22.30
*0624KPPB	6-20X1 1/2	8,000	4.54	1212KPPB	12-14X3/4	5,000	8.10
*0707KPPB	7-19X7/16	10,000	2.30	*1408KPPB	1/4-14X1/2	3,000	9.12
*0806KPPB	8-18X3/8	10,000	2.96	1412KPPB	1/4-14X3/4	3,000	11.50
*0808KPPB	8-18X1/2	10,000	3.10	1420KPPB	1/4-14X1 1/4	1,000	15.50
*0810KPPB	8-18X5/8	10,000	3.50				
*0812KPPB	8-18X3/4	8,000	4.05				
*0816KPPB	8-18X1	6,000	5.05				
*0820KPPB	8-18X1 1/4	5,000	5.90				
*0824KPPB	8-18X1 1/2	4,000	7.29				
*0832KPPB	8-18X2	2,000	9.22				
*0840KPPB	8-18X2 1/2	2,000	11.26				
*0848KPPB	8-18X3	2,000	11.97				

Steel Black Phosphate




All Items have #2 point

**MODIFIED TRUSS PHILLIPS
SELF DRILLING SCREWS**

Manufactured to SAE J78 specifications
For attaching metal lath to metal studs between 12-20 gauge thick
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0606KPMB	6-20X3/8	8,000	2.54	*1008KPMB	10-16X1/2	6,000	4.10
*0608KPMB	6-20X1/2	8,000	2.88	1012KPMB	10-16X3/4	6,000	5.25
				1016KPMB	10-16X1	5,000	6.67
*0808KPMB	8-18X1/2	5,000	3.80	1020KPMB	10-16X1 1/4	4,000	9.10
*0809KPMB	8-18X9/16	5,000	3.90	1024KPMB	10-16X1 1/2	3,000	10.40
*0812KPMB	8-18X3/4	5,000	4.75	1032KPMB	10-16X2	2,000	15.00
*0816KPMB	8-18X1	4,000	5.60				
*0820KPMB	8-18X1 1/4	3,000	6.80				
*0824KPMB	8-18X1 1/2	2,000	7.50				
*0826KPMB	8-18X1 5/8	3,000	7.40				
*0828KPMB	8-18X1 3/4	3,000	8.50				
*0830KPMB	8-18X1 7/8	2,000	9.00				
*0832KPMB	8-18X2	2,000	9.00				
*0840KPMB	8-18X2 1/2	2,000	11.50				
*0848KPMB	8-18X3	1,500	13.50				

Steel Black Oxide




Items marked with “*” have #2 point; all others have #3 point

**HEX WASHER SLOTTED
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0808KSWB	8-18X1/2	10,000	3.30	*1008KSWB	10-16X1/2	8,000	4.50
*0816KSWB	8-18X1	8,000	4.65	1012KSWB	10-16X3/4	6,000	5.69

Steel Black Oxide



Items marked with “*” have #2 point; all others have #3 point

**HEX WASHER UNSLOTTED
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0608KWB	6-20X1/2	10,000	2.63	1210KWB	12-14X5/8	5,000	7.30
				1212KWB	12-14X3/4	5,000	8.06
*0808KWB	8-18X1/2	10,000	3.32	1216KWB	12-14X1	4,000	9.75
*0810KWB	8-18X5/8	9,000	3.79	1220KWB	12-14X1 1/4	3,000	11.35
*0812KWB	8-18X3/4	8,000	4.16	1224KWB	12-14X1 1/2	2,000	6.60
*0816KWB	8-18X1	6,000	5.01	1228KWB	12-14X1 3/4	2,000	14.20
*0820KWB	8-18X1 1/4	2,000	6.21	1232KWB	12-14X2	2,000	16.00
*0824KWB	8-18X1 1/2	2,000	7.26				
*0828KWB	8-18X1 3/4	2,000	8.63	*1408KWB	1/4-14X1/2	3,000	10.20
				*1410KWB	1/4-14X5/8	3,000	11.20
*1006KWB	10-16X3/8	8,000	4.80	1412KWB	1/4-14X3/4	3,000	12.23
*1008KWB	10-16X1/2	8,000	4.78	1416KWB	1/4-14X1	2,000	14.60
*1010KWB	10-16X5/8	7,000	5.03	1420KWB	1/4-14X1 1/4	1,500	16.84
1012KWB	10-16X3/4	6,000	5.85	1424KWB	1/4-14X1 1/2	1,250	19.34
1016KWB	10-16X1	5,000	8.05	1428KWB	1/4-14X1 3/4	1,000	21.34
1020KWB	10-16X1 1/4	1,000	8.37	1432KWB	1/4-14X2	900	24.18
1024KWB	10-16X1 1/2	1,000	10.12				
1028KWB	10-16X1 3/4	1,000	10.70				
1032KWB	10-16X2	1,000	12.72				



Steel Black Oxide




Items marked with “*” have #2 point; all others have #3 point

**PAN SQUARE RECESS
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0608KQPB	6-20X1/2	10,000	2.08	*1008KQPB	10-16X1/2	8,000	4.64
*0810KQPB	8-18X5/8	3,000	3.46	1016KQPB	10-16X1	2,000	6.86
*0812KQPB	8-18X3/4	3,000	4.00	1020KQPB	10-16X1 1/4	1,000	7.73
*0816KQPB	8-18X1	2,000	4.85	1024KQPB	10-16X1 1/2	1,000	9.25
*0824KQPB	8-18X1 1/2	4,000	6.60	1224KQPB	12-14X1 1/2	2,000	12.20

Steel Black Zinc



Items marked with “*” have #2 point; all others have #3 point


**PAN PHILLIPS
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0406KPPBZ	4-24X3/8	10,000	1.08	*1008KPPBZ	10-16X1/2	8,000	4.58
*0408KPPBZ	4-24X1/2	10,000	1.27	1010KPPBZ	10-16X5/8	8,000	4.80
				1012KPPBZ	10-16X3/4	7,000	5.51
*0606KPPBZ	6-20X3/8	10,000	1.63	1016KPPBZ	10-16X1	5,000	6.93
*0608KPPBZ	6-20X1/2	10,000	2.11	1020KPPBZ	10-16X1 1/4	4,000	8.07
*0612KPPBZ	6-20X3/4	10,000	2.80	1024KPPBZ	10-16X1 1/2	3,000	9.30
*0616KPPBZ	6-20X1	10,000	3.33	1028KPPBZ	10-16X1 3/4	3,000	11.00
*0806KPPBZ	8-18X3/8	10,000	2.78	1212KPPBZ	12-14X3/4	5,000	8.10
*0808KPPBZ	8-18X1/2	10,000	3.10	1216KPPBZ	12-14X1	3,000	9.14
*0810KPPBZ	8-18X5/8	10,000	3.45	1220KPPBZ	12-14X1 1/4	3,000	11.45
*0812KPPBZ	8-18X3/4	9,000	4.05	1224KPPBZ	12-14X1 1/2	2,000	12.43
*0816KPPBZ	8-18X1	6,000	5.05	1232KPPBZ	12-14X2	1,000	15.75
*0820KPPBZ	8-18X1 1/4	5,000	5.90				
*0824KPPBZ	8-18X1 1/2	4,000	6.73	1412KPPBZ	1/4-14X3/4	3,000	11.50
*0828KPPBZ	8-18X1 3/4	3,000	7.75	1416KPPBZ	1/4-14X1	2,000	13.70
				1420KPPBZ	1/4-14X1 1/4	1,000	15.52
				1424KPPBZ	1/4-14X1 1/2	1,000	17.82

NEW!

Steel Black Zinc




Items marked with “*” have #2 point; all others have #3 point

**FLAT PHILLIPS
SELF DRILLING SCREWS**

Combination Phillips and Slotted Recess
Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
0848KPPBZ	8-18X3	1,250	11.83				

Steel Black Zinc




Items marked with “*” have #2 point; all others have #3 point

**HEX WASHER UNSLOTTED
SELF DRILLING SCREWS**

Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0806KWZ	8-18X3/8	10,000	2.93	1412KWZ	1/4-14X3/4	3,000	11.71
*0808KWZ	8-18X1/2	10,000	3.25	1416KWZ	1/4-14X1	2,000	14.20
*0812KWZ	8-18X3/4	8,000	4.17	1420KWZ	1/4-14X1 1/4	1,500	16.25
*0816KWZ	8-18X1	6,000	5.13	1424KWZ	1/4-14X1 1/2	1,250	18.67
*0820KWZ	8-18X1 1/4	6,000	6.05	1428KWZ	1/4-14X1 3/4	1,000	21.34
*0824KWZ	8-18X1 1/2	5,000	7.26	1432KWZ	1/4-14X2	900	24.18
*1008KWZ	10-16X1/2	8,000	5.06	3112KWZ	5/16-12X3/4	1,000	22.78
1012KWZ	10-16X3/4	5,000	5.70	3116KWZ	5/16-12X1	1,000	26.50
1016KWZ	10-16X1	5,000	6.90	3120KWZ	5/16-12X1 1/4	700	30.05
1020KWZ	10-16X1 1/4	4,000	8.40	3124KWZ	5/16-12X1 1/2	600	33.88
1024KWZ	10-16X1 1/2	3,000	9.30				
1212KWZ	12-14X3/4	5,000	7.50				
1216KWZ	12-14X1	4,000	9.20				

Steel Black Zinc




Items marked with “*” have #2 point; all others have #3 point

**FLAT PHILLIPS UNDERCUT
SELF DRILLING SCREWS**

Combination Phillips and Slotted Recess
Manufactured to ASME B18.6.3 & SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
*0808KPUBZ	8-18X1/2	10,000	1.97	*1008KPUBZ	10-16X1/2	10,000	3.60
*0812KPUBZ	8-18X3/4	10,000	2.83	1012KPUBZ	10-16X3/4	7,000	2.86
				1212KPUBZ	12-14X3/4	5,000	4.91

Steel Black Zinc



All items have #3 point

**WAFFER PHILLIPS
SELF DRILLING SCREWS WITH MACHINE SCREW THREADS**

Manufactured to SAE J78 specifications
Case Hardened to Rockwell C52 - 58 (Core Hardness: Rockwell C32-40)

Part #	Size	Ctn Qty	Wght Lbs/M	Part #	Size	Ctn Qty	Wght Lbs/M
1024KWAFMSBZ	10-24X1 1/2	1,000	9.20				

